

GEKA® plus automatic hose reel

GEKA® plus automatic hose reel EA15 and EA15SK

Advantages / benefits: Robust, durable and rust-free **stainless steel** construction with **double-sided suspension** of the reel
Suitable for drinking water
Automatic roll-up of the hose locks 2x per rotation
 With individually positionable hose stopper for different hose sizes (1/2", 5/8", 3/4")
 Gentle hose guide prevents the hose from jumping off the reel during reeling
Suitable for wall, floor and ceiling mounting
 Hose guide on the axle adjustable in three 45° steps
42.9041.9 with 12.5 m GEKA® plus water hose WS500 3/4", wall thickness 3.1 mm, operating pressure 11 bar, Made in Germany + 2 m inlet hose

Material: Housing: made of robust, durable and rustproof stainless steel 1.4301, hose guide rollers, inlet pipe, locking mechanism (toothed washer, catch, spring, snap ring), GEKA® plus rotary fitting: stainless steel, hose stopper: black rubber

Operating pressure at +20 °C: max. 20 bar (hose-dependent), 42.9041.9: 11 bar

Temperature range: +4°C to +60°C (hose-dependent)

Dimensions L x W x H cm: 52 (incl. mount) x 45 x 23,5

Special note: The automatic hose reel is laid out for 15 m 3/4" hoses with 25 mm or 25 m 1/2" hoses with an outer diameter of 17 mm
 Screws and wall plugs for wall mounting are not included in the scope of delivery
Stainless steel 165° swivel wall bracket incl. connecting screws (42.9097.9) and various inlet hose versions available separately as accessories

5



EA15 - 42.9040.9

Connection	Male thread	Male thread
Male thread mm	26,44	26,44
Male thread	G3/4	G3/4
Capacity of 1/2" hose approx. m	25	25
Capacity of 5/8" hose approx. m	24	24
Capacity of 3/4" hose approx. m	15	15
Hose length approx. m	-	12,5
Weight approx. kg	14	18
PU units	1	1
Item no.	42.9040.9	42.9041.9

With high-quality rubber hose



EA15SK
42.9041.9



Robust stainless steel construction



GEKA® plus rotary fitting and stainless steel pipe



Suitable for wall, floor and ceiling mounting

GEKA® plus automatic hose reel

GEKA® plus automatic hose reel EA15GSK and EA15KSK

Advantages / benefits:Robust, durable and rust-free **stainless steel** construction with **double-sided suspension** of the reel
Automatic roll-up of the hose locks 2x per rotation
 With individually positionable hose stopper for different hose sizes (1/2", 5/8", 3/4")
 Gentle hose guide prevents the hose from jumping off the reel during reeling
Suitable for wall, floor and ceiling mounting
 Hose guide on the axle adjustable in three 45° steps
42.9043.9: GEKA® plus rubber water hose 3/4" made of EPDM, 5-ply with synthetic yarns, ID 19 mm, wall thickness 4 mm, operating pressure 20 bar, Made in Germany + **2 m inlet hose**
42.9043.9 and 42.9044.9: with drinking water-certified 20 m Rehau Rauaqua hose 1/2", GEKA® plus stainless steel quick couplings + 2 m inlet hose
42.9044.9: additionally with GEKA® plus professional cleaning gun (23.1891.8)

Material:Housing: made of robust, durable and rustproof stainless steel 1.4301, hose guide rollers, inlet pipe, locking mechanism (toothed washer, catch, spring, snap ring), GEKA® plus rotary fitting: stainless steel, hose stopper: black rubber

Operating pressure at +20 °C:20 bar

Temperature range:+4°C to +60°C (hose-dependent)

Dimensions L x W x H cm:52 (incl. mount) x 45 x 23,5

Special note:The automatic hose reel is laid out for 15 m 3/4" hoses with 25 mm or 25 m 1/2" hoses with an outer diameter of 17 mm
 Screws and wall plugs for wall mounting are not included in the scope of delivery
Stainless steel swivelling wall mount 165° incl. connecting screws (42.9097.9) available separately (not included).

Connection	Male thread	Male thread	Male thread
Male thread mm	26,44	26,44	26,44
Male thread	G3/4	G3/4	G3/4
Capacity of 1/2" hose approx. m	25	25	25
Capacity of 5/8" hose approx. m	24	24	24
Capacity of 3/4" hose approx. m	15	15	15
Hose length approx. m	11	20	20
Weight approx. kg	20	17	18
PU units	1	1	1
Item no.	42.9042.9	42.9043.9	42.9044.9



EA15GSK
42.9042.9



EA15KSK
42.9043.9



EA15KSK
42.9044.9



Automatic roll-up of the hose



Locking mechanism can be controlled by pulling at the end of the hose



Gentle hose guide



Accessories for GEKA® plus automatic hose reels EA15

Wall mount for EA15, EA15SK, EA15GSK and EA15KSK

Advantages / benefits:Stainless steel swivelling wall mount 165° incl. connecting screws (42.9097.9)
Compatible with the automatic hose reels EA15 (42.9040.9),
EA15SK (42.9041.9), EA15GSK (42.9042.9) and EA15KSK (42.9043.9 and
42.9044.9)

Material:Stainless steel



Swivelling angle degrees	165°
Weight approx. kg	2,6
PU units	1
Item no.	42.9097.9

Supply hoses EA15SK, EA15GSK and EA15KSK

5



Hose connection set SK

Hose size inches	3/4"
Hose ID mm	19
Hose outer diameter mm	24,8
Wall thickness mm	3,1
Approx. length m	2
Operating pressure at +20 °C bar	11
Bursting pressure at +20 °C bar	35
PU units	1
Item no.	42.9080.9



Hose connection set GSK

Hose size inches	3/4"
Hose ID mm	19
Hose outer diameter mm	27
Wall thickness mm	4
Approx. length m	2
Operating pressure at +20 °C bar	20
Bursting pressure at +20 °C bar	60
PU units	1
Item no.	42.9081.9



Hose connection set KSK

Hose size inches	1/2"
Hose ID mm	12,8
Hose outer diameter mm	18,8
Wall thickness mm	3
Approx. length m	2
Operating pressure at +20 °C bar	20
Bursting pressure at +20 °C bar	30
PU units	1
Item no.	42.9082.9