

GEKA® automatic wall-mounted hose box K15

Advantage / benefit: **automatic roll-up and comfortable unwinding** of hose without knotting; hose can be locked in any position; **controlled and safe hose intake (slow retract); tool-free adjustable hose stopper; robust wall mount: 180° rotatable;** incl. mounting kit (4x dowels, 4x screws and 4x stainless steel washers); **with anti-drip feature for supply hose thanks to practical plug-in option;** **easy to detach from the wall;** **fully assembled and ready to use;** **compact size;** **including high-quality, robust push-fit system and spray nozzle;** **made from chrome-plated brass;**

Operating pressure at +20 °C: 10 bar
 Temperature range: +4 °C to +45 °C
 Dimensions LxWxH cm: 50 (incl. mount) x 18 x 40
 Scope of delivery: GEKA® plus spray nozzle, light; GEKA® plus hose piece 1/2"; GEKA® plus hose piece 1/2" with water stop; GEKA® plus tap plug G3/4, 15 m hose + 2 m supply hose

Hose size	1/2"
Hose ID mm	12.5
Hose length approx. m	15
Approx. length supply hose m	2
Packaging	Box
PU units	1
Article No.	42.8710.9



Automatic roll-up	Infinitely variable locking mechanism	Incl. assembly kit and metal mount	Supply hose 2 m	can be adjusted without tools
Incl. push-fit system made of metal	Safe, controlled retraction	Plug-in option for supply hose	180° rotatable	