


GEKA® automatic wall-mounted hose box K25

Advantages / benefits: **Automatic roll-up and comfortable unwinding** of hose without knotting; hose can be locked in any position;
Controlled and safe hose intake (slow retract);
Tool-free adjustable hose stopper;
Robust wall mount: 180° rotatable;
incl. mounting kit (4x dowels, 4x screws and 4x stainless steel washers);
 with **anti-drip feature** for **supply hose** thanks to **practical plug-in option;**
Easily removable from the wall bracket;
No unintentional swinging back and forth of the hose box **thanks to Position Plus**
 Water hose **phthalate-free**
Fully assembled and ready to use;
Including high quality, robust **push-fit connector system** and **spray nozzle** made from chrome-plated brass;


Operating pressure at +20 °C: 8 bar
 Temperature range: +4 °C to +45 °C
 Dimensions L x W x H cm: 62 x 26 x 43 (incl. mount)
 Scope of delivery: GEKA® plus spray nozzle, light; GEKA® plus hose piece 1/2";
 GEKA® plus hose piece 1/2" with water stop; GEKA® plus tap plug G3/4,
 15 m hose + 2 m supply hose




Hose size	1/2"
Hose ID mm	12,5
Hose length approx. m	25
Approx. length supply hose m	2
PU units	1
Article No.	42.8721.9




Automatic roll-up




Infinitely variable locking mechanism




Incl. assembly kit and metal mount




Supply hose 2 m




can be adjusted without tools




Incl. push-fit connector system made of metal



Reduces unwanted swinging back and forth



Plug-in option for supply hose



180° rotatable

